**Full Colour Multi Function Printer** 

## RICOH IM C3000 IM C3500 IM C4500 IM C6000





Welcome to a new era of technology that keeps your workplace up to date with RICOH IM C3000 / C3500 / C4500 / C6000 range of intelligent devices. Device and technology that is designed to grow and adapt, just as your business does.

Today's workplace needs to be ready for tomorrow. RICOH Intelligent Devices provide smooth access to functionality upgrades and productivity enhancements when they are released, without needing to change your hardware. Turn your device into a powerful hub that helps you manage information workflows efficiently, using technology that is scalable, secure, sustainable and simple.

#### Now is the time to:

- Protect your devices with easy access to security updates
- Take advantage of easy productivity upgrades at your own pace
- Save costs by bringing high-standard quality print output in-house
- Maximise productivity with streamlined workflows







### **Excellent Performance with the Best Quality Output**

## Greater Control of Scan and Print Management

Scanning of smaller sized documents can be easily done with the new small sized paper scan unit. The double feed detection unit helps to improve scan accuracy while the EFI controller enhances print management. Now, you can also create professional grade flyers at your own convenience with our inner multi-folding unit.



### **Seamless User Experience**

Our intelligent devices offer efficient working and reduced user intervention by expanding paper capacity. Choose from our versatile finishing and paper options for a professional touch to save time and reduce outsourcing expenses. With RICOH Intelligent Support, experience maximum device uptime and minimal disruption across all your devices.





#### **Maximise Cost Savings**

Enjoy lower running costs and reduced energy consumption thanks to environmentally friendly low TEC (Typical Electricity Consumption) values. Furthermore, take advantage of RICOH Intelligent Support services that anticipate potential issues and send corrective instructions via the Smart Operation Panel, avoiding interruptions and prolonging the optimal performance of your device – avoiding the need for intervention by more costly IT resources.



# Next-level Productivity with Smart Operations

Interact with the 10.1" Smart Operation Panel like a typical smart device and configure it for quick and easy access to apps you use most often. A variety of mobile connectivity options enable printing or scanning to the office network or cloud from a smart device with built in support for NFC, AirPrint® or Mopria®. All this underpinned by a unique suite of support apps from RICOH Smart Integration.

### RICOH IM C3000 / IM C3500 / IM C4500 / IM C6000

MAIN SPECIFICATIONS

MODEL  GENERAL  Warm-up Time  First Output Speed : B/W  First Output Speed : Full Color	RICOH IM C3000	RICOH IM C3500	RICOH IM C4500	RICOH IM C6000		
Warm-up Time  First Output Speed : B/W  First Output Speed : Full Color		MCOTT IIII C5300	MCOTT IN C4300	MCOTT IN COOO		
First Output Speed : B/W First Output Speed : Full Color		21 Seco	nds			
First Output Speed : Full Color	4.5 Seconds	4.5 Seconds	3.6 Seconds	2.9 Seconds		
· ·	6.9 Seconds	6.9 Seconds	5.4 Seconds	4.2 Seconds		
Continuous Output Speed	30ppm	35ppm	45ppm	60ppm		
Memory Std/Max	эоррііі			ооррін		
HDD Std/Max	2GB Std / 4GB Max					
ARDF Capacity	320GB Std/Max					
SPDF Capacity	100 Sheets 220 Sheets					
Weight [Mainframe]						
Dimensions W x D x H [Standard]	Less Than 85.5Kg Less Than 87.5Kg 587 x 685 x 788 mm					
Dimensions W x D x H [Maximum]						
(excluding ARDF/SPDF)	668 x 738 x 1030 mm					
Power Source		220 - 240V !	50/60Hz			
COPIER						
Multiple Copying		Up to 999	Copies			
Resolution		600 d	pi			
Zoom		From 25% to 400	% in 1% Step			
PRINTER						
CPU	Intel Atom Process	or ApolloLake 1.3GHz	Intel Atom Processo	r ApolloLake 1.6GHz		
Printer Language : Standard	PCL5c, PCL6, Postscript 3 (emulation), PDF direct (emulation)					
Printer Language : Option	Gen	uine Adobe® Postscript®3™, XPS, IPDS	5, PictBridge, PDF Direct from A	dobe®		
Print Resolution		1,200 x 1,2	00 dpi			
Network Interface : Standard	Etherne	t 10 base-T/100base-TX/1000 base-T, l	JSB Host I/F Type A, USB Device	I/F Type B		
Network Interface : Option	Bi-directi	onal IEEE 1284/ECP, Wireless LAN (IEE	E 802.11a/b/g/n), Additional NIC	(2nd port)		
Mobile Printing Capability		Apple AirPrint®, Mopria®, NFC, R	icoh Smart Device Connector			
Windows® environments	Windows® 7, Windows®	8.1, Windows®10, Windows® Server 2		Windows® Server 2012R2,		
Mac OS environments		Windows® Se Macintosh OS X1				
UNIX environments	LINI	K Sun® Solaris, HP-UX, SCO OpenServe		 1® ΔΙΧ		
SAP® environments		SAP® S.		1 7 107		
Other Supported environments		IBM iSe	· · · · · · · · · · · · · · · · · · ·			
SCANNER						
Scanning Speed	120ipm (Simplex) / 240ipm (duplex)					
Resolution : Maximum	1,200 dpi (via TWAIN)					
Compression Method	TIFF (MH, MR, MMR, JBIG2), Grayscale					
File Formats	Single Page TIFF, Single page JPEG, Single Page High compression PDF, Single page PDF-A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi Page PDF-A					
Scan Modes	Email, Folder, USB, SD Card					
		.,	,			
FACSIMILE		PSTN. F	PBX			
FACSIMILE Circuit		PSTN, F 2 Secon				
FACSIMILE		PSTN, F 2 Secon 33.6 Kb	nds			
FACSIMILE Circuit Transmission Speed		2 Secon	nds ops			
FACSIMILE Circuit Transmission Speed Modem Speed : Maximum		2 Secoi 33.6 Kl	nds ops 200 x 100 dpi			
FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard		2 Secoi 33.6 Kt 8 x 3.65 line/mm,	nds ops 200 x 100 dpi 400 x 400 dpi			
FACSIMILE Circuit Transmission Speed Modem Speed : Maximum Resolution : Standard Resolution : Option		2 Secoi 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm,	nds ops 200 x 100 dpi 400 x 400 dpi MR, JBIG			
FACSIMILE  Circuit  Transmission Speed  Modem Speed: Maximum  Resolution: Standard  Resolution: Option  Compression Method		2 Secoi 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, Mt	nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages)			
FACSIMILE  Circuit  Transmission Speed  Modem Speed: Maximum  Resolution: Standard  Resolution: Option  Compression Method  Memory: Standard		2 Secon 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320	nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages)			
FACSIMILE  Circuit  Transmission Speed  Modem Speed: Maximum  Resolution: Standard  Resolution: Option  Compression Method  Memory: Standard  Memory: Maximum		2 Secon 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320	nds  pps  200 x 100 dpi  400 x 400 dpi  MR, JBIG  Pages)  D Pages)			
FACSIMILE  Circuit  Transmission Speed  Modem Speed: Maximum  Resolution: Standard  Resolution: Option  Compression Method  Memory: Standard  Memory: Maximum  PAPER HANDLING  Recommended Paper Size		2 Secoi 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 60MB (4,800 SRA3, A3, A4, A5,	nds pps 200 x 100 dpi 400 x 400 dpi MR, JBIG Pages) D Pages) A6, B4, B5, B6			
FACSIMILE  Circuit  Transmission Speed  Modem Speed: Maximum  Resolution: Standard  Resolution: Option  Compression Method  Memory: Standard  Memory: Maximum  PAPER HANDLING  Recommended Paper Size  Paper Input Capacity Std		2 Secoi 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MR 4MB (320 60MB (4,800 SRA3, A3, A4, A5, 1,200 Sh	nds  pps  200 x 100 dpi  400 x 400 dpi  MR, JBIG  Pages)  D Pages)  A6, B4, B5, B6  eets			
FACSIMILE  Circuit  Transmission Speed  Modem Speed: Maximum  Resolution: Standard  Resolution: Option  Compression Method  Memory: Standard  Memory: Maximum  PAPER HANDLING  Recommended Paper Size		2 Secoi 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 60MB (4,800 SRA3, A3, A4, A5,	nds  pps  200 x 100 dpi  400 x 400 dpi  MR, JBIG  Pages)  D Pages)  A6, B4, B5, B6  eets  eets			
FACSIMILE  Circuit  Transmission Speed  Modem Speed: Maximum  Resolution: Standard  Resolution: Option  Compression Method  Memory: Standard  Memory: Maximum  PAPER HANDLING  Recommended Paper Size  Paper Input Capacity Std  Paper Output Capacity Std	1.625	2 Secoi 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MR 4MB (320 60MB (4,800 SRA3, A3, A4, A5, 1,200 Sh 4,700 Sh	nds  pps  200 x 100 dpi  400 x 400 dpi  MR, JBIG  Pages)  D Pages)  A6, B4, B5, B6  eets eets	Sheets		
FACSIMILE  Circuit  Transmission Speed  Modem Speed : Maximum  Resolution : Standard  Resolution : Option  Compression Method  Memory : Standard  Memory : Maximum  PAPER HANDLING  Recommended Paper Size  Paper Input Capacity Std  Paper Output Capacity Std  Paper Output Capacity Max	1,625	2 Secol 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MR 4MB (320 60MB (4,800 SRA3, A3, A4, A5, 1,200 Sh 4,700 Sh 5 Sheets	nds  ops  200 x 100 dpi  400 x 400 dpi  MR, JBIG  Pages)  O Pages)  A6, B4, B5, B6  eets  eets  eets  3,625	Sheets		
FACSIMILE  Circuit  Transmission Speed  Modem Speed: Maximum  Resolution: Standard  Resolution: Option  Compression Method  Memory: Standard  Memory: Maximum  PAPER HANDLING  Recommended Paper Size  Paper Input Capacity Std  Paper Output Capacity Std		2 Secoi 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MI 4MB (320 60MB (4,800 SRA3, A3, A4, A5, 1,200 Sh	nds  pps  200 x 100 dpi  400 x 400 dpi  MR, JBIG  Pages)  Pages)  A6, B4, B5, B6  eets  eets  eets  3,625  g/m²  etterhead, Cardstock, Preprinted			
Circuit  Transmission Speed  Modem Speed: Maximum  Resolution: Standard  Resolution: Option  Compression Method  Memory: Standard  Memory: Maximum  PAPER HANDLING  Recommended Paper Size  Paper Input Capacity Std  Paper Output Capacity Std  Paper Output Capacity Max  Paper Weight  Paper Types		2 Secol 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MR 4MB (320 60MB (4,800 SRA3, A3, A4, A5, 1,200 Sh 4,700 Sh 500 Sheets 60 - 300, e paper, Special paper, Color paper, Lo	nds  pps  200 x 100 dpi  400 x 400 dpi  MR, JBIG  Pages)  Pages)  A6, B4, B5, B6  eets  eets  eets  3,625  g/m²  etterhead, Cardstock, Preprinted			
FACSIMILE Circuit Transmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Std Paper Weight Paper Types ECOLOGY	Plain paper, Recycl	2 Secon 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MI 4MB (320 60MB (4,800 SRA3, A3, A4, A5, 1,200 Sh 4,700 Sh 500 She 5 Sheets 60 - 300 e paper, Special paper, Color paper, Le Coated paper, Envelope, Glos	nds  pps  200 x 100 dpi  400 x 400 dpi  MR, JBIG  Pages)  D Pages)  A6, B4, B5, B6  eets  eets  eets  g/m²  etterhead, Cardstock, Preprinteds s paper, Label paper, OHP	l paper, Bond paper,		
FACSIMILE  Circuit  Transmission Speed  Modem Speed: Maximum  Resolution: Standard  Resolution: Option  Compression Method  Memory: Standard  Memory: Maximum  PAPER HANDLING  Recommended Paper Size  Paper Input Capacity Std  Paper Input Capacity Std  Paper Output Capacity Std  Paper Output Capacity Max  Paper Weight  Paper Types  ECOLOGY  Power Consumption: Max	Plain paper, Recycl Less Tha	2 Secon 33.6 KB 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MN 4MB (320 60MB (4,800 SRA3, A3, A4, A5, 1,200 Sh 4,700 Sh 5 Sheets 60 - 300, e paper, Special paper, Color paper, Le Coated paper, Envelope, Glos	nds  pps  200 x 100 dpi  400 x 400 dpi  MR, JBIG  Pages)  D Pages)  A6, B4, B5, B6  eets  eets  eets  g/m²  etterhead, Cardstock, Preprinteds paper, Label paper, OHP  Less That	d paper, Bond paper,		
FACSIMILE Circuit Transmission Speed Modem Speed: Maximum Resolution: Standard Resolution: Option Compression Method Memory: Standard Memory: Maximum PAPER HANDLING Recommended Paper Size Paper Input Capacity Std Paper Input Capacity Std Paper Output Capacity Std Paper Output Capacity Std Paper Weight Paper Types ECOLOGY	Plain paper, Recycl Less Tha 47	2 Secon 33.6 Kt 8 x 3.65 line/mm, 16 x 15.4 line/mm, MH, MR, MI 4MB (320 60MB (4,800 SRA3, A3, A4, A5, 1,200 Sh 4,700 Sh 500 She 5 Sheets 60 - 300 e paper, Special paper, Color paper, Le Coated paper, Envelope, Glos	nds  pps  200 x 100 dpi  400 x 400 dpi  MR, JBIG  Pages)  D Pages)  A6, B4, B5, B6  eets  eets  eets  2,625  g/m²  etterhead, Cardstock, Preprinters paper, Label paper, OHP  Less Than  59.	l paper, Bond paper,		

### RICOH IM C3000 / IM C3500 / IM C4500 / IM C6000


MAIN SPECIFICATIONS

MODEL	RICOH IM C3000	RICOH IM C3500	RICOH IM C4500	RICOH IM C6000		
INPUT / OUTPUT TRAY AND FINISHER OPTIONS						
1 x 550-Sheets Paper Tray (PB 3270)	Paper Size: A6-SRA3, Paper Weight: 60-300g/m²					
2 x 550-Sheets Paper Tray (PB 3280)	Paper Size : A6-SRA3, Paper Weight : 60-300g/m²					
2,000-Sheets Large Capacity Tray (LCIT PB3290)	Paper Size : A4, Paper Weight : 60-300g/m²					
1,500-Sheets Large Capacity Tray (LCIT RT3040)	Paper Size : A4, Paper Weight : 60-300g/m <sup>2</sup>					
1,000-Sheets Hybrid Finisher (SR3260)	Paper Size: Proof Tray: A6-A3, Shift Tray: A6-A3, Paper weight: 60-300g/m² Staple paper size: A4-A3, Staple paper weight: 52-105g/m Staple position: Top, Bottom, 2 Staples Staple capacity Max: 50 sheets (A4) 30 Sheets (A3) Stapleless capacity Max: 5 sheets (A4/A3)					
3,000-sheet Finisher (SR 3280) [Available for IM C4500, IM C6000 only]	Paper Size: Proof Tray: A6-A3, Shift Tray: A6-A3, Paper weight: 60-300g/m² Staple paper size: A4-A3, Staple paper weight: 52-105g/m Staple position: Top, Bottom, 2 Staples, Top slant Staple capacity Max: 50 sheets (A4) 30 Sheets (A3)					
1,000-Sheet Booklet Finisher (SR3270)	Paper Size: Proof Tray: A6-A3, Shift Tray: A6-A3, Booklet tray: A4-A3 Paper weight: 60-300g/m² Staple paper size: A4-A3, Staple paper weight: 52-105g/m Staple position: Top, Bottom, 2 Staples, Booklet Staple capacity Max: 50 sheets (A4) 30 Sheets (A3)					
2,000-Sheet Booklet Finisher (SR3290) [Available for IM C4500, IM C6000 only]	Paper Size : Proof Tray : A6-A3, Shift Tray : A6-A3, Booklet tray : A4-A3 Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples, Booklet Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)					
500-Sheet Internal Finisher (SR3250) (IM C6000 is not supported)	Paper Size : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top, Bottom, 2 Staples Staple capacity Max : 50 sheets (A4) 30 Sheets (A3)					
250-Sheet Internal Finisher (SR3300) (Available for IM C3000, IM C3500 only)	Paper Size : A6-A3, Paper weight : 60-300g/m² Staple paper size : A4-A3, Staple paper weight :52-105g/m Staple position : Top,1 Staple Staple capacity Max : 2-5 sheets (A4)					
Internal Shift Tray (SH3080)	Tray Capacity: 250 sheets, Paper size: 320 mm x 600 mm or smaller, Paper weight: 60-300g/m²					
One-bin tray (BN3130)	Tray Capacity: 125 sheets, Paper size: A5 - A3, Paper weight: 52-300g/m²					

#### OTHER OPTIONS

Platen Cover PN2000, DF3110, DF3120, Fax Option Type M37, G3 Interface Unit Type M37, Fax Connection unit Type M37, FAX Memory unit Type M19 64MB, Memory Unit Type M37 4GB, Caster Table Type M3, VM Card Type M37, Side Tray, Punch Unit NA/EU/SC (PU3070,PU3080,PU3090), Internal Multi-fold unit FD3010, Camera direct print card, Postscript3 Unit Type M37, XPS direct print Option Type M37, IEEE 1284 I/F Type M19, IEEE 802.11a/g/n I/F Type M19, Device server option Type M37, File format Converter Type M19, OCR Unit Type M13, Small Paper Feeding Unit Type M37, Page Keeper Type M37, ADF Handle, External Keyboard Bracket Type M19, Optional Counter Interface Unit Type M12, Key Counter Bracket Type M3, NFC Card Reader Type M37, Smart Card Reader Built in Unit Type M37, External USB Keyboard (No bracket), Color Controller E-25C, Unicode Font Package for SAP®License.





RICOH ASIA PACIFIC PTE LTD

30 Cecil Street, #13-01/08 Prudential Tower, Singapore 049712

Phone: +65 6830 5888, Fax: +65 6830 5830



















